



General Product Specifications

Eureka Miner FS SRS2 & Jindara Barossa FS SRS2

Dimensions and Specifications	
Overall Dimension (Height)	937 mm
Overall Dimension (Width)	710 mm
Overall Dimension (Depth)	570 mm
Firebox Dimension (Height)	343 mm
Firebox Dimension (Width)	500 mm
Firebox Dimension (Depth)	347 mm
Door Opening Dimension (Height x Width)	240 x 550mm
Glass Viewing Size (Height x Width)	263 x 516mm
Flue Size	150mm
Back of Heater to Flue Centre	180 mm
Shipping weight	165kg
Linings	Firebricks on walls
Baffle thickness	8mm
Glass Type	Flat, toughened 5mm ceramic
Hearth & Clearance requirements	
Min. Hearth Width	950 mm
Min. Hearth Depth	1050 mm
Min. Hearth Thickness	18 mm
Min. In Front Of Unit	400 mm
Rear Clearance	150mm*
Side Clearance	400 mm
Corner Clearance	175 mm
	* denotes standard flue shield required (included in wood heater)
Emissions and Efficiency	
Emissions	1.4g/kg
Efficiency	72%*
Peak Output	21kw
	*Peak efficiency % quoted
CLEARANCES AND SPECIFICATIONS PROVIDED IN THIS TABLE ARE FOR REFERENCE ONLY. ALWAYS REFER TO THE OWNER'S MANUAL FOR EXACT SPECIFICATIONS PRIOR TO INSTALLATION	