

## **GASON Cropper Topper**

The Gason Cropper Topper is an "all gear drive" (no Belts) stubble mulcher. It meets the needs of most modern-day continuous cropping cereal growers who require a high level of trashing efficiency, sturdy machine design and construction, coupled with reliable performance values.

Hinged rear flaps mounted on flared deck body uplift the mulched stubble on a high trajectory to spread evenly behind. Fuel efficient high speed passes see the work load diminish with Gason Cropper Toppers traveling over 18kph and cover more than 22 hectares per hour. An optional 3 Fan kit produces an airstream across the deck to reduce settling of debris for ease of servicing and reduce the risk of fire.

Innovatively designed and expertly manufactured using the finest European gearboxes, torsion rubber coupling drivelines & PTO shafts to suit tractors from 150 to 600 HP means Gason's range of Cropper Toppers provide industry leading performance in the field.

The range of Gason Cropper Toppers have a pedigree of reliable and dependable service that comes from more than 75 years of manufacturing products for Australian conditions.





## **Cropper Topper Specifications**

		•
Models	Cut Width	Towed Transport Width
24FT	7.13m	3950mm / 13ft
31FT	9.39m	4630mm / 15ft 2in
35FT	10.67m	5300mm / 17ft 2in
41FT	12.47m	5830mm / 19ft 2in
Standard Features		
Deck Materials		Angular streamline 6mm deck with underside reinforced
Ground Protection		Height adjustable skids flank each rotor
Drive Train		Power matched with torsion rubber couplings between gearboxes
Height Control		Level lift phased hydraulic cylinders and height adjustable drawbar
Wing Float & Fold		Wings free float to ground contour: 5° down to 400mm & 8° up to 600mm
Rotor Bar		Laminated spring steel beam dual mulching blade assembly
Blades		Down stepped suction uplift lower cutting blade with up stepped flat shredder blade
Front Chains		Galvanized safety chains with rod replacement system
Rear Guard		Lower rear flap
Wheels		235/75-17.5 slick recap tyres
Options		
Deck mounted fan kit		Deck platform debris clearing
Front stabiliser wheel kit (35ft & 41ft models)		Outer wing front wheel for contour banks or cotton row spacings
Oil seal protector kit		Added lower housing protection against wire or banding

## Additional Information

Suitable for 150-600HP tractors, subject to tractor specifications. PTO 1000rpm



