



DELTA SLASHERS

Stronger, Easily Transported,
Reliable, Effective



PROUDLY DESIGNED & CRAFTED
ARARAT, VICTORIA, AUSTRALIA.

GASON.COM.AU



DELTA SLASHERS

Stronger, Easily Transported, Reliable, Effective



The **Gason Delta Slasher** sets the standard for heavyweight folding slashers in Australia. Weighing close to 4.5 tonnes* but folding to just 2.5 metres for easy transport-the Gason Delta is the ideal combination of strength, size and versatility.

The Delta is a favourite choice of professional contractors, councils, airports and farmers across Australia.

Designed to tame even the toughest terrain, this robust slasher excels in all environments from simple grass slashing or roadside verges to scrubland regeneration.

The Gason Delta is available in 15 or 20 Foot, in Side or Rear throw configuration with Standard or Mulch Blades. Built to an industrial standard-when you must get the job done, choose Gason.

Delta Slasher Specifications		
Models	Cut Width	Variations Available in Side or rear throw with Standard or Optional Dual Mulch Blade Kit
Delta 15	4.57m	Rear throw (Slashing)
Delta 20	6.1m	or dual mulch throw (Orchard)
Standard Features		
Deck Materials	6mm fully welded steel deck with reinforced sides and frontage. Streamlined and angular for easy clean.	
Gearbox	210HP BareCo Power Divider to Comer Italian rotor heads (3)	
PTO Shaft	Comer Italian - V80 Series CVJ	
Clutch	Over-run device on input and 4 plate clutches on each PTO	
Skids	8mm removable side plates with wide hardened skids	
Rotor Bar	Laminated spring steel	
Blades	Suction uplift swing back blades	
Wing Movement	20° cutting down; 45° cutting up	
Tractor Connection	Swivel eye tow pull on hydraulic level lift including spring suspension	
Front and Rear Chains	Galvanised safety chains with rodreplacement system	
Options		
Dual Mulch Blade Kit	For finer break down of long materials	
Oil Seal Protector Kit	Fitted around gearbox under deck	
Additional Information		
<ul style="list-style-type: none"> • Suitable for 90-200HP tractors, subject to tractor specifications • PTO 1000rpm 		

Notes: