



ORCHARD MOWERS



The Orchard Industry's
favourite mower



PROUDLY DESIGNED & CRAFTED
ARARAT, VICTORIA, AUSTRALIA.

GASON.COM.AU



ORCHARD MOWERS

The Orchard Industry's favourite mower



The Gason Single, Twin & Triple Rotor Orchard Mowers have remained the long-time favourite of Australian orchardists since their inception. The compact depth and generous cutting width gives you the luxury of a 'one pass cut' down the row.

Standard features include front and rear height adjustable 'domed end' rollers, and side or rear discharge ability. For contoured rows, the winged model is available, which floats freely from basin ground form to flat ground profile.

The twin rotor Drop Centre mower accurately follows the ground profile of the delved row form, cutting the full depth of the "V" shape. It is designed to freely adapt to changes in the ground form.

The Very Heavy Duty (VHD) twin or triple rotor Orchard Mowers are fully equipped to tackle the toughest conditions, and are designed for mulch throw or shred prunings.

In addition, the Delta Wing mulch throw can be used comfortably as an Orchard mower. It is ideal for wide spacing rows, inter-row ground contours and in between blocks. Delta Wing mulch throw features a narrow transport width of 2.5m for added manoeuvrability and discharge on both sides. Additional information on the Delta Wing mulch throw can be found on the Gason Delta Slasher flier.



Orchard Mowers Specifications											
Deck Size	Deck Type					Mount Type		Rotors			Cut Width
	Taper Back	Square Back	Winged Deck	Flat Deck	Drop Centre	3PL	Trailed	1	2	3	
7' 0"	✓			✓		✓		✓			2.13m
9' 6"		✓	✓			✓				✓	2.77m
10' 6"		✓	✓			✓				✓	3.1m
11' 6"		✓	✓			✓				✓	3.4m
12' 6"	✓		✓			✓				✓	3.71m
14'		✓		✓			✓			✓	4.08m

Standard Features	
Deck Materials	Angular streamlined 6mm deck with underside reinforced
Gearbox	Bare-Co 130HP or Comer Italian 90HP (model dependent)
Clutch	4 plate with over-run
Skids	Full 6mm sides including 50 x 8mm hardened steel skids
Rotor Bar	Laminated spring steel bars
Blades	Suction uplift swing back blades
Linkage Mounting	Cat 2 - 3PL, Centre Mounted, RH Offset
Front and Rear Chains	Galvanised safety chains
Additional Information	
<ul style="list-style-type: none"> • Suitable for 45-200HP tractors, subject to tractor specifications • PTO 540rpm & 1000rpm (model dependent) 	

Notes:

GASON[®]
STRONG.
LIFELONG.

PLEASE VISIT GASON.COM.AU
TO FIND YOUR NEAREST DEALER