

Specifications

T Series Planter Specifications

Machine Dimensions	T10000	T12000m
Overall Length	9.60m	
Overall Unfolded Width	10.20m	
Frame Depth (front to rear)	4.30m	
Overall Road Transport Width	6.45m	
Overall Road Transport Height	4.05m	5.00m
Road Clearance:	250mm	
Max. Recommended Working Depth:	150mm	
Overall Weight	9.0t **	

**Approximate weight only, varies depending on configuration and attachments

Tine Spacing	Number of Tines		Effective Working Width	
	T100000	T120000	T100000	T120000
200mm (8")	50	60	10.0m	12.0m
250mm (10")	40	48	10.0m	12.0m
300mm (12")	34	40	10.2m	12.0m

No. of Toolbar Rows:	5	
Toolbar Spacing:	1.0m typ.	
Toolbar Section:	100 x 100 x 9.0mm RHS Grade 450	
Drawbar Section:	150 x 250 x 6.0mm RHS Grade 450	
ScariTILL:	Breakout Force	<ul style="list-style-type: none"> • 180kg (400lbf) • 245kg (540lbf)
	Underframe Clearance	760mm to 660mm (30" to 26") in 12.5 mm (½") increments.
	Tine Jump	350mm (13.8")
HydraTILL:	Breakout Force Hydraulic	140kg to 310kg (310lbf to 680lbf)
	Underframe Clearance	760mm to 660mm (30" to 26") in 12.5 mm (½") increments.
	Tine Jump	350mm (13.8")
Tyres:	500/50-22.5 16PLY Tubeless Floatation Tyre	
Wheel Centre Width:	3.0m (3m controlled traffic)	
Hydraulic Hoses (depth & wing fold)	½" I.D. SAE100R2 hose (non-skive)	
Maximum Road Transport Speed:	20km/h	